



NOTE: STANDARD PARTS ARE SHOWN FOR REFERENCE ONLY
CHECK ORIGINAL ORDER FOR ORDERING SPARE PARTS

NOTES:
DIMENSIONS IN INCHES (MM APPROX.)
FOR REFERENCE ONLY, NOT TO BE USED FOR CONSTRUCTION UNLESS CERTIFIED
SHIMMING OF THE SADDLES MAY BE REQUIRED
CENTER VESSEL ON 2 OR 3 SUPPORTS AT SPAN(S) "S".
INCORRECT MANIFOLDING WILL CAUSE SEVERE LOCAL STRESS AROUND PORT AND MAY RESULT IN LEAKS AND PREMATURE FAILURE. TAKE EVERY PRECAUTION LISTED IN THE ENGINEERING PACKET OR USERS MANUAL
INTERNAL PERMEATE PRESSURE MUST NOT EXCEED 125 PSI.
AS PER ASME AND CRN REQUIRED
ASME SECTION X 2021, RP/NB STAMP REQUIRED FOR CRN
SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



PRO 8-300-MSP

ENGR TS 7/27/21	ECO 20094	REVISED 7/27/21	DRAWING 101021	REV X
QLTY MK 7/27/21				
MRKT AP 7/27/21				

GENERAL DIMENSIONS

Shell Length Code	L inch (mm)	P3		S Span in (mm)	Empty Weight lb (kg)
		Standard inch (mm)	*P1 Optional inch (mm)		
-1	58.4 [1483.36]	46 [1168.40]	47 [1193.80]	1 @ 28 [711.20]	79 [36]
-2	98.4 [2499.36]	86 [2184.40]	87 [2209.80]	1 @ 56 [1422.40]	91 [41]
-3	138.4 [3515.36]	126 [3200.40]	127 [3225.80]	1 @ 80 [2032.00]	103 [47]
-4	178.4 [4531.36]	166 [4216.40]	167 [4241.80]	2 @ 64 [1625.60]	115 [52]
-5	218.4 [5547.36]	206 [5232.40]	207 [5257.80]	2 @ 78 [1981.20]	126 [57]
-6	258.4 [6563.36]	246 [6248.40]	247 [6273.80]	2 @ 92 [2336.80]	138 [63]
-7	298.4 [7579.36]	286 [7264.40]	287 [7289.80]	2 @ 106 [2692.40]	150 [68]
-8	338.4 [8595.36]	326 [8280.40]	327 [8305.80]	2 @ 120 [3048.00]	162 [73]

*P1 Not Available With 4" Mega Side Port

BILL OF MATERIALS

ITEM	QTY	P/N	DESCRIPTION	MATERIAL
1	1	4080196	Shell	Filament Wound, Epoxy FRP
2	2	4080028	Bearing Plate	6061-T6 Aluminum, SB-221, Anodized
3	2	4080177-3	Sealing Plate	Noryl GFN2
4	2	4080254-1	Feed/Concentrate Port, 3", "K"	Stainless Steel, 316, SA-312
		4080487-1	Feed/Concentrate Port, 4", "L"	
5	4	6201343	Retaining Ring, F/C Port, 3", "K"	Stainless Steel, 316, SA-479
		6201450	Retaining Ring, F/C Port, 4", "L"	
6	2	6188504-N	O-Ring Seal, F/C Port, 3", "K"	Ethylene Propylene
		6180348-N	O-Ring Seal, F/C Port, 4", "L"	
7	2	4080309	Permeate Port	Noryl GFN2
8	2	6100442MK	Head Seal	Ethylene Propylene
9	2	6110229-N	Permeate Port Seal	Ethylene Propylene
10	2	4080320	Retaining Ring w/ Finger Pull	Stainless Steel, 316, SA-479
11	2	6121200	Retaining Ring, Permeate Port	Stainless Steel, 316, SA-479
12	2*	4080173	Support Saddle	Thermoplastic Rubber
13	2	4080137	Strap Assembly	Stainless Steel, 316L
14	4	6150001	Strap Screw	Stainless Steel, 18-8
15	2	A/R	Adapter	Thermoplastic
16	1	4080165-3	Thrust Cone	PVC Thermoplastic
17	2	6180326-N	Adapter Seal	Ethylene Propylene
18	A/R	A/R	PWT Seal	Ethylene Propylene
19	3	4080062-4	Shim, Adapter	Noryl GFN2

*3 each with shell lengths -4 and longer.