



NOTE: STANDARD PARTS ARE SHOWN FOR REFERENCE ONLY.
CHECK ORIGINAL ORDER FOR ORDERING SPARE PARTS

GENERAL DIMENSIONS

Shell Length Code	L inch (mm)	S Span in (mm)	Empty Weight lb (kg)
-1	65 (1651)	34 (864)	106 (48)
-1.5	85 (2159)	45 (1143)	129 (59)
-2	105 (2667)	56 (1422)	152 (69)
-3	145 (3683)	80 (2032)	198 (90)
-4	185 (4699)	104 (2642)	244 (111)
-5	225 (5715)	128 (3251)	290 (132)
-6	265 (6731)	150 (3810)	336 (153)
-7	305 (7747)	3 PTS.	382 (174)
-7.5	235 (8255)	3 PTS.	405 (184)
-8	345 (8763)	3 PTS.	428 (195)

BILL OF MATERIALS

ITEM	QTY	P/N	DESCRIPTION	MATERIAL
1	1	4080531	Shell	Filament Wound, Epoxy FRP
2	2	4080533	Bearing Plate	6061-T6 Aluminum, SB-221, Anodized
3	2	4080065	Sealing Plate	PVC Thermoplastic
4	2	4080231	Feed/Concentrate Port	SST Super Duplex, SA-790
5	2	6121187	Retaining Ring, F/C Port	Stainless Steel, 316, SA-479
6	2	6184604-N	O-Ring Seal, F/C Port	Ethylene Propylene
7	2	4080378	Permeate Port	Noryl GFN2
8	2	6100442MK	Head Seal	Ethylene Propylene
9	2	6110229-N	Permeate Port Seal	Ethylene Propylene
10	6	4080474-1	Locking Segments	Stainless Steel, 316
11	2	6121200	Retaining Ring, Permeate Port	Stainless Steel, 316, SA-479
12	2*	4080175	Support Saddle	Thermoplastic Rubber
13	3	4080137	Strap Assembly	Stainless Steel, 316
14	6	6150001	Strap Screw	Stainless Steel, 18-8
15	2	A/R	Adapter	Thermoplastic
16	1	4080043	Thrust Ring	PVC Thermoplastic
17	2	6180326-N**	Adapter Seal	Ethylene Propylene
18	4	A/R	PWT Seal	Ethylene Propylene
19	6	6150048	Head Screw	Stainless Steel, 18-8
20	3	4080062-4	Shim, Adapter	Noryl GFN2

*3 each with shell length -4 and longer
**6110221-N when Permeate Port is not noryl

NOTES:

FOR REFERENCE ONLY, NOT TO BE USED FOR CONSTRUCTION UNLESS CERTIFIED

SHIMMING OF THE SADDLES MAY BE REQUIRED.

CENTER VESSEL ON 2 OR 3 SUPPORTS AT SPAN(S) "S". 3 SUPPORTS REQUIRED FOR LENGTHS -4 AND OVER.

INCORRECT MANIFOLDING WILL CAUSE SEVERE LOCAL STRESS AROUND PORT AND MAY RESULT IN LEAKS AND PREMATURE FAILURE. TAKE EVERY PRECAUTION LISTED IN THE ENGINEERING PACKET.

INTERNAL PERMEATE PRESSURE MUST NOT EXCEED 125 PSI.

AS PER ASME AND CRN REQUIRED
ASME SECTION X 2019, RP/NB STAMP REQUIRED FOR CRN

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



BPV-8-1000-EP

ENGR LS 21/28/01	ECO	REVISED	DRAWING	REV
QLTY LS 21/28/01	12056	21/28/01	101049	D
MRKT BOA 21/28/01				